

Engine Shangchai SC8D190G2B1
Rated Power 140 kW (188 hp / 190 ps) @ 2,200 rpm
Nominal Amplitude Range 2.0 / 1.3 mm
Vibration Frequency Range 28 / 32 Hz
Centrifugal Force Range 390 / 328 kN
Working Width 2,130 mm
Operating Mass 20,000 kg

6620E ROLLER

## 6620E SPECIFICATIONS >>>

ENGINE	
Emission Regulation	Tier 2 / Stage II
Manufacturer	Shangchai
Model	SC8D190G2B1
Rated Power	140 kW (188 hp / 190 ps) @ 2,200 rpm
Peak Torque	650 N·m
Number of Cylinders	6
Aspiration	Turbo & air-to-air intercooled
Cooling Type	Water

ELECTRICAL SYSTEM	
System Voltage	24 V

DRIVE TRAIN	
Theoretical Gradeability	45 %
Transmission Type	Hydraulic
1st Maximum Speed	4 km/h
2nd Maximum Speed	5.5 km/h
3rd Maximum Speed	6.5 km/h
4th Maximum Speed	10.5 km/h
Min. Outside Turning Radius	7,000 mm

STEERING	
Steering System	Hydraulic
Steering Method	Articulation
Steering Angle	± 35°
Steering Relief Pressure	16 MPa

BRAKES	
Service Brake Type	Hydraulic
Service Brake Actuation	Hydraulic
Parking Brake Actuation	Mechanical apply; Hydraulic release

	0	PT	ION	AL	EQ	VI	PN	Œ	VT		
--	---	----	-----	----	----	----	----	---	----	--	--

Padfoot Drum Segment Kit (PDH)

TIRES	
Tire Size	23.1-26-12PR
Tire Pressure	200-220 kPa

HYDRAULIC SYSTEM	
Main Pump Type	Piston Pump
Main Relief Pressure	35 MPa

PERFORMANCE	
Static Linear Front Drum Load	592 N/cm
Number of Vibrating Drums	1
Nominal Amplitude Range	2.0 / 1.3 mm
Vibration Frequency Range	28 / 32 Hz
Centrifugal Force Range	390 / 328 kN
Number of Amplitude Settings	2

OPERATING MASS	
Operating Mass with Ballast	20,000 kg
Mass on Vibrating Drum	13,200 kg
Mass on Drive Axle	6,800 kg

SERVICE CAPACITIES		
Fuel Tank	373 L	
Engine Oil	19 L	
Hydraulic Oil Tank	90 L	
Cooling System	32 L	

DIMENSIONS	
A Overall Length	6,450 mm
B Overall Width	2,400 mm
C Drum Width	2,130 mm
D Drum Diameter	1,600 mm
E Drum Thickness	45 mm
F Wheelbase	3,250 mm
G Min. Ground Clearance	440 mm
H Overall Height	3,050 mm



